

Thermal Degradation of Fire-Retardant-Treated Plywood

Between 1985 and 1995, approximately 750,000 multi-family housing units experienced roofing problems due to fire-retardant-treated (FRT) plywood sheathing failure (Figs. 1–3). The problem is caused by excessive exposure to solar radiation.

Research at the USDA Forest Service, Forest Products Laboratory (FPL), from 1988 to 1999 resulted in more than 20 technical papers and three national standards. The standards, developed by the American Society for Testing and Materials (ASTM) and American National Standards Institute (ANSI), form the scientific/technical basis for new performance-based qualification requirements for commercial FRT plywood roof sheathing.

- ASTM/ANSI D5516—Standard test method for thermal degrade of FRT plywood
- ASTM/ANSI D5664—Standard test method for thermal degrade of FRT lumber
- ASTM/ANSI D6305—Standard practice for developing engineering design adjustments for allowable properties of FRT plywood

Another result of FPL research was the development of models for strength loss over time (Fig. 4). Later, field service-life issues were evaluated, and predictive models (Fig. 5) were developed for the first time to predict residual service life of FRT constructions. Research on the further development of residual serviceability models is continuing.

For more information, contact
 Dr. Jerrold E. Winandy
 USDA Forest Service
 Forest Products Laboratory
 One Gifford Pinchot Dr.
 Madison, WI 53726-2398
 Phone: (608) 231-9316; Fax: (608) 231-9582
 E-mail: jwinandy@fs.fed.us



Figure 1. Outside view of failed FRT plywood roof sheathing.



Figure 2. Inside view of failed FRT plywood roof sheathing.



Figure 3. Failed FRT plywood roof sheathing after removal.




Figure 4. Isothermal degradation models for untreated and FRT wood after up to 4 years at 66°C. (PA, phosphoric acid; MAP, monoammonium phosphate; BBA, borax-boric acid; GUP/B, guanylurea phosphate/boric acid; DPF, dicyandiamide-formaldehyde-phosphoric acid; OPE, diethyl-N,N-bis(2-hydroxyethyl) aminomethyl phosphonate; UNT, untreated)




Figure 5. Residual service-life model for untreated and FRT wood used as roof sheathing after 10 years. (PA, phosphoric acid; MAP, monoammonium phosphate; GUP/B, guanylurea phosphate/boric acid; UNT, untreated)

References

Lebow, Patricia K.; Winandy Jerrold E. 1999. Verification of a kinetics-based model for long-term effects of fire retardants on bending strength at elevated temperatures. *Wood and Fiber Science* 31(1): 49–61.

Lebow, S.T.; Winandy, J.E. 1999. Effect of fire-retardant treatments on plywood pH and the relationship of pH to strength properties. *Wood Science and Technology* 33 (4): 285–298.

Lebow, Stan T.; Winandy, Jerrold E. 1998. The role of grade and thickness in the degradation of fire-retardant-treated plywood. *Forest Products J.* 48(6): 88–94.

LeVan, Susan; Collet, Mary 1989. Choosing and applying fire-retardant-treated plywood roof sheathing. Gen. Tech. Rep. FPL–GTR–62. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 11 p.

LeVan, Susan L.; Kim, Jong Man; Nagel, Robert J.; Evans, James W. 1996. Mechanical properties of fire-retardant-treated plywood after cyclic temperature exposure. *Forest Products J.* 46(5): 64–71.

LeVan, Susan L.; Ross, Robert J.; Winandy, Jerrold E. 1990. Effects of fire retardant chemicals on the bending properties of wood at elevated temperatures. Res. Pap. FPL–RP–498. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 24 p.

LeVan, Susan L.; Winandy, Jerrold E. 1990. Effects of fire retardant treatments on wood strength: A review. *Wood and Fiber Science* 22(1): 113–131.

Sweet, Mitchell S.; Winandy, Jerrold E. 1999. Influence of degree of polymerization of cellulose and hemicellulose on strength loss in fire-retardant-treated Southern pine. *Holzforschung.* 53(3): 311–317.

TenWolde, Anton. 1997. FPL roof temperature and moisture model—description and verification. Res. Pap. FPL–RP–561. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 48 p.

Winandy, Jerrold E. 1995. Effects of fire retardant treatments after 18 months of exposure at 150°F (66°C). Res. Note FPL–RN–0264. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 13 p.

Winandy, Jerrold E. 1997. Effects of fire retardant retention, borate buffers, and redrying temperature after treatment on thermal-induced degradation. *Forest Products J.* 47(6): 79–86.

Winandy, Jerrold E. 1998. Using kinetics-based models to address serviceability concerns for fire retardant treated wood at elevated in-service temperatures. In: Natterer, J.; Sandoz, J-L, eds. Proceedings, 5th World conference on timber engineering; 1998 August 16–21; Montreux, Switzerland. Lausanne, Switzerland: Swiss Federal Institute of Technology. Vol. 1: 794–795.

Winandy, Jerrold E. 2001. Thermal degradation of fire-retardant-treated wood: Predicting residual service life. *Forest Products J.* 51(2): 47–54.

Winandy, Jerrold E.; Barnes, H. Michael; Hatfield, Cheryl A. 2000. Roof temperature histories in matched attics in Mississippi and Wisconsin. Res. Pap. FPL–RP–589. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 24 p.

Winandy, Jerrold E.; Lebow, Patricia K. 2001. Modeling strength loss in wood by chemical composition. Part I. An individual component model for Southern Pine. *Wood and Fiber Science* 33(2): 239–254.

Winandy, Jerrold E.; Lebow, Patricia K.; Nelson, William. 1998. Predicting bending strength of fire-retardant-treated plywood from screw-withdrawl tests. Res. Pap. FPL–RP–568. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 20 p.

Winandy, J.E.; LeVan, S.L.; Lee, P.W. 1988. Effects of fire retardant treatment and redrying on the mechanical properties of Douglas-fir and aspen plywood. Res. Pap. FPL–RP–485. Madison, WI: U.S. Department of Agriculture, Forest Service, Forest Products Laboratory. 20 p.